



SECURITY FEATURES

- UL listed products
 - UL Burglary
 - UL 20 min fire rating
- Case hardened steel cylinder housing
- Rotating collar
- Optional key lockable thumbturn
- 6 mm steel retaining screws
- High security bolt
 - hardened steel with 2" length
 - 1" (25,4 mm) throw
- Reinforced steel strike box
- Protective bolt shield

STANDARD FINISHES

US26/625	Bright chrome
US3/605	Bright brass PVD
US26D/626	Satin chrome
US4/606	Satin brass


Fits 1 3/4" (44.5 mm) to 2 1/8" (54 mm) hole. Standard hardware for 1 3/4" (44.5 mm) thick door included.

ABLOY® CYLINDER OPTIONS

ABLOY® PROTEC (N)
ABLOY® DISKLOCK PRO (D)

STANDARD BOLT


ABLOY® LC801



A 2 3/8" (60 mm) or 2 3/4" (70 mm)
(Adjustable)

DRIVE-IN BOLT

ABLOY® LC802



A 2 3/8" (60 mm) or 2 3/4" (70 mm)
(Adjustable)

CY411N, D
DOUBLE CYLINDER



ME151
w/LC801



ME152
w/LC802

Bolt operated by key outside and inside.

CY412N, D
SINGLE CYLINDER
WITH THUMBTURN



ME153
w/LC801



ME154
w/LC802

Bolt operated by key outside and thumbturn inside.

CY413N, D
SINGLE CYLINDER
WITH KEY LOCKABLE
THUMBTURN



ME155
w/LC801



ME156
w/LC802

Bolt operated by key outside and thumbturn inside.
Inside thumbturn can be locked with proper key to provide double cylinder security.



www.abloy.com

Abloy Oy
Wahlforssinkatu 20
P.O.Box 108
FI-80101 JOENSUU
FINLAND
Tel. +358 20 599 2501
Fax +358 20 599 2209



